Kerb/Hose/Cable Ramps

TRAFFIC-LINE Kerb Ramps - HDPE



The **TRAFFIC-LINE** Kerb Ramp is manufactured in High Density
Polyethylene (HDPE) for strength and durability. It can accommodate kerb heights from 75mm to 125mm and can be fixed permanently if desired via four fixing holes moulded in. The surface is embossed with an anti-trip pattern making it safe in use.

Easily transported for use by delivery drivers and ideal for use in hospitals, warehouses, airports, storage depots etc.

Specification:

Material: High Density Polyethylene

(HDPE) Colour: Yellow SWL: 250 kg

- Easy to transport lightweight
- HDPE no corrosion worries
- Handles incorporated for easy lifting
- · Effective anti-slip surface
- · Recyclable

Standards:

Conforms to National Grid T/SP/E/42 A Code of Practice 2013

TRAFFIC-LINE Kerb Ramps – GRP




TRAFFIC-LINE GRP Kerb Ramps are a useful aid in moving loads from one level to another. They are an effective alternative to other materials used as ramps such as plywood, steel, tarmac, concrete etc. plus they have no scrap value, reducing the risk of theft. Highly suitable for use in areas such as hospitals, delivery drivers, warehouses, airports, storage depots etc.

Available in two versions – standard with SWL 350kg and Heavy duty with SWL 750kg making the latter capacity suitable for motorised wheelchairs.

TRAFFIC-LINE GRP Kerb Ramps are manufactured in bright yellow material with a textured non-slip surface with reflective strips for additional visibility and bolt down points in all four corners.

Compliant with UK & European legislation.



- Easy to transport lightweight construction
- GRP material no corrosion worries
- Anti-slip surface
- · Non slip rubber feet
- Reflective strips





	- C =	1
	27 P.O. Communication of the C	and the last of th
1000	Married World	
100	THE PARTY OF THE P	

Dimensions (mm) W x D x H	Delivery weight (kg/ea.)	Reference	Typical despatch time (working days)
985 x 1,200 x 90	8	279.32.506	1 / 2 days

SWL (kg)	Dimensions (mm) W x D x H	Delivery weight (kg/ea.)	Reference	Typical despatch time (working days)
500	690 x 1,250 x 50	9	279.18.230	1 / 2 days