118 Arrow Trax™



- Suitable for medium to heavy traffic conditions.
- For placement inside entrances in schools, universities, public buildings, offices, sports facilities, shopping malls.
- Vacuum clean.
- Free of toxic DOP and DMF.

118 Arrow Trax™

			PRODUCT SPECIFICATIONS		
Designation	า	Dust Control Matting			
Description		Absorbent - scraper carpet mat			
Material					
		Needle punched carpe tern1200 grams of fibe	rpet consisting of anti-static 100% polypropylene fibers with chevron pat- fibers per m².		
	Backing	Black vinyl			
Process		Needle punch			
Category		Indoor absobent - Bestseller			
Recommended use		Indoor - medium to heavy foot traffic, indoors			
Colours		Grey, Charcoal, Brown, Automn Brown			
Weight		3.9 kg/m ²			
Thickness		10 mm			
Standard sizes		60 cm x 90 cm 90 cm x 150 cm 120 cm x 180 cm 130 cm x 300 cm 130 cm x 600 cm 130 cm x 20 m 200 cm x 20 m			
Custom sizes 130		130 cm and 200 cm per linear meter			
Special remarks		Splicing, seaming not recommended			
1		T	PRODUCT TESTING		
	Te	ests	Norms	Results	
Abrasion resistance			ASTM D3884	1.68 g weight loss	
Colour fastness to light		<u> </u>	AATCC 16E	5	
Accelerated wear test by sim floor machine			U.S.	2.5	
Accelerated soiling			U.S.	4	
Anti-slip			DIN51130 BGR181		
Water retention			ISO 4920 TNO W6034	4.0 l/m ²	
Sanitary epidemiologic test		test	GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.229.P.044984.07.09	
Graves tear	strength		22.2.2.2.2.2.3.07.02.07		
Hardness a					
	511010				
Elongation					
		C (Pl 1 1 11	FIRE TESTING	p	
		Surface Flammability	ASTM D2859	Pass	
		Russian fire retardancy test	CCPB.NLOP-019.B01723	Pass	
		Classification of the reaction to fire performance	DIN EN 13501-1		
Sustainability			 Recyclable material REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals) Contributes to cleaner environment by reducing need of cleaning chemicals 		



