




- For Indoor and Outdoor use
- High quality steel
- Shock absorbing features
- UV and temperature resistant pads
- Highly visible yellow and black marking
- TUV-tested according to DGUV 108-007



## BLACK BULL FLEX Protection Guards



A unique and patented development of our standard **BLACK BULL** Protection Guards that features the strength and protective attributes of steel combined with the ability to flex up to 10° from the vertical, reducing the incidence of damage and the need for repairs to both guard and vehicle. This is achieved by equipping the guard with flexible shock absorbing polyurethane (PU) pads. These pads are UV, weather and temperature resistant, making them suitable for indoor and outdoor use.

- Flexible and yielding guard
- Flexes up to 10° from vertical
- Minimises damage to vehicles
- Reduces damage to floor

### Specifications:

76 mm Ø x 3.0 mm Wall  
 Base Plate: 160 x 140 x 10 mm  
 (Drilled 4 fixing holes)

### Finish:

Indoor use: Powder coated yellow with black bands.  
 Outdoor use: Hot Dip Galvanised and powder coated yellow with black bands.

### Maximum inclination limits:

| Height   | Inclination |
|----------|-------------|
| 390 mm   | 55 mm       |
| 640 mm   | 95 mm       |
| 1,240 mm | 190 mm      |



| Powder coated           |                      |                          |            |
|-------------------------|----------------------|--------------------------|------------|
| Colour                  | Dimension (mm) H x W | Delivery weight (kg/ea.) | Reference  |
| Yellow                  | 390 x 375            | 10.6                     | 196.21.558 |
| Yellow with black bands | 390 x 750            | 12.6                     | 196.23.927 |
|                         | 390 x 1,000          | 13.6                     | 196.20.479 |
|                         | 390 x 2,000          | 17.6                     | 196.23.138 |
|                         | 640 x 750            | 14.6                     | 196.27.339 |
|                         | 640 x 1,000          | 16.6                     | 196.29.617 |
|                         | 640 x 2,000          | 19.6                     | 196.28.884 |
|                         | 1,240 x 750          | 20.6                     | 196.21.978 |
|                         | 1,240 x 1,000        | 22.6                     | 196.21.739 |
|                         | 1,240 x 2,000        | 26.1                     | 196.27.054 |

| Hot dip galvanised and powder coated |                      |                          |            |            |
|--------------------------------------|----------------------|--------------------------|------------|------------|
| Colour                               | Dimension (mm) H x W | Delivery weight (kg/ea.) | Reference  |            |
| Yellow                               | 390 x 375            | 10.6                     | 196.24.195 |            |
| Yellow with black bands              | 390 x 750            | 12.6                     | 196.28.870 |            |
|                                      | 390 x 1,000          | 13.6                     | 196.28.678 |            |
|                                      | 390 x 2,000          | 17.6                     | 196.29.639 |            |
|                                      | 640 x 750            | 14.6                     | 196.26.638 |            |
|                                      | 640 x 1,000          | 16.6                     | 196.21.658 |            |
|                                      | 640 x 2,000          | 19.6                     | 196.20.921 |            |
|                                      | 1,240 x 750          | 20.6                     | 196.23.976 |            |
|                                      | 1,240 x 1,000        | 22.6                     | 196.29.532 |            |
|                                      |                      | 1,240 x 2,000            | 26.1       | 196.22.922 |

|                             |        |     |            |
|-----------------------------|--------|-----|------------|
| Chemical anchors (Set of 8) | 10/170 | 2.0 | 109.20.858 |
|-----------------------------|--------|-----|------------|