

Machine and Rack Protection

BLACK BULL Pallet Racking Protectors – with Guide Rollers



Pallet racking protectors which include rollers to facilitate pallet placement to and from floor level locations. The incorporation of rollers helps to dampen shock and vibration which can occur when pallets are being located. They are most suitable for use in warehouses, distribution depots, manufacturing units etc.

Specifications:

Material: Steel

Roller material: Polyamid

Roller Dimensions:

110mm High

75mm from bottom edge of roller to floor.

Variants:

Right-angle and 'U' profiles.

Finish:

Indoor use: Powder coated yellow with black stripes.

- For Indoor use
- Highly visible colours
- Easily installed
- Virtually indestructible
- Guide roller(s) incorporated



Description	Dimensions (mm) Height/Width/Gauge	Delivery weight (kg/ea.)	Reference	Typical despatch time (working days)
Right-angle Fixing bolt = 4	400 x 160 x 6	9	197.22.542	1 / 2 days
U-Profile Rawl bolt = 6	400 x 160 x 6	12	197.22.021	
Rawl bolt S12		0.2	109.17.393	1 / 2 days
Surface fixing bolt S12		0.3	109.24.665	

BLACK BULL Sliding Door Protection Guards



Frequently fire doors, access doors and gates are damaged or impeded by pallets, boxes etc. with obvious consequences, especially in the case of sliding fire doors. **BLACK BULL** Sliding Door Protectors provide the right level of protection to prevent such occurrences.

Manufactured from 6 and 10mm Gauge steel these protectors are immensely strong and can withstand substantial collisions, prevent expensive repairs and ensure that vital fire doors operate correctly without being impeded.

Finish:

Indoor use: Powder coated yellow.

- For Indoor use
- Strong steel protection
- Radius corners with 45° angled ends
- Ensure full operation of fire doors etc
- Highly visible yellow coating



Dimensions (mm) H x L x D	Gauge (mm)	Delivery weight (kg/ea.)	Reference	Typical despatch time (working days)
150 x 800 x 100 Anchor holes = 5	6	10.5	197.24.121	5 / 10 days
	10	16	197.17.683	
150 x 1,200 x 100 Anchor holes = 7	6	14.5	197.29.576	
	10	24	197.13.775	
Surface fixing bolt S12		0.2	109.17.393	1/2 days
Through bolt anchor		0.3	109.24.665	