

"CLASSIC" OUTDOOR NOTICE BOARDS

TECHNICAL SPECIFICATIONS

HINGE FREE: Wear resistant, warp proof integrated hinge.
LOCKABLE: Exclusive tamper-proof safety lock with hidden latch.
FULL DISPLAY: 100 % of the display surface visible (lock mounted in the frame not the glazing).
STRENGTH: Robust profile and available in 4mm anti-vandal Plexichoc™ or safety glass.
PRACTICAL: Doors easily replaceable in case of major vandalism.
WATERPROOF: Elastomer seal and anti-condensation vents.

NOTICE BOARD

Format: single sided.
Display area: from 4 to 21 A4.
Profile depth: 58 mm
Glazing: vandal-resistant 4 mm Plexichoc® or 4 mm tempered safety glass.
Opening method: side opening (door is reversible) or raising door.
Raising doors: suspended on gas struts for easy opening and support.
Locking: tamperproof safety lock with supplied 2 keys, two locks on H 1350 mm and raising door models.
Waterproofing: elastomer seal.
Back plate finish: galvanised steel back in a white lacquered finish for use with magnets. External back finished in RAL 7032 unless otherwise specified.
Frame finish: silver anodised aluminium or painted in our Vitincom® colour offering.
Installation: wall or post mounting (optional).
Supplied with Procity® magnets (1 per A4).

Post kits:

Post kit: 2 post 60 x 40 mm either silver anodised or painted, delivered with 4 stainless steel mounting brackets.
Installation: concrete directly in the ground or on base plates.*
Plus post: 60 x 40 mm either silver anodised or painted, delivered with 2 stainless steel mounting brackets.
Used as a central post to align several notice boards.
Installation: concrete directly in the ground.

*If the product is to be likely to be exposed to strong winds, we strongly recommend post kits to be concreted directly in the ground.

Optional decorative header panel:

Header panel: 2 mm plasma cut steel.
3 shapes: Dome, Wave or Rectangle
Installation: attached to a wall using pre-drilled mounting holes (fixings not supplied) or on the post kit using fixings provided.

Other options:

LED kit (supplied for self-assembly)*
Additional magnets.

*LED ribbons and transformers are not factory fitted and require installation by a qualified electrician to comply with

PAINT FINISH



RAL 5010



RAL 9005



RAL 3004



RAL 6005



RAL 8017



Anodised

