

479 Cushion Trax[®]

Bestselling anti-fatigue mat



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths 479 Cushion Trax®

Bestselling anti-fatigue mat with ergonomic benefit derived from 14 mm thick worker platform comprised of a long wearing top surface laminated onto a resilient microcellular vinyl base for maximum durability, comfort, and insulation from hard floors and vibrations.

- Featured with RedStop™ slip resistant backing to prevent mats from shifting
- Available with yellow borders along sides to comply with OSHA code 1910-144
- Bevelled edges on all four sides to minimize risk of tripping
- Diamond plate pattern provides traction while allowing easy twist turns
- UniFusion™ technology, engineered to resist in the harshest work environments
- Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).

Recommended use

- Dry Areas
- In manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual workstations. Also suitable for commercial environments including hotels, reception desks, shop counters, department stores, banks, restaurants, etc.
- Heavy duty

Colors:

- Black
- Black/Yellow
- Grey

Sizes:

- 60cm x 91cm
- 91cm x 150cm
- 91cm x 300cm
- 91cm x 600cm
- 122cm x linm
- 152cm x linm
- 60cm x linm
- 91cm x linm
- 122cm x 22.8m
- 152cm x 22.8m
- 60cm x 22.8m
- 91cm x 22.8m



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths Cushion Trax®

General

Brand	Notrax
Category	Dry Areas Linear Lengths
Product Number	479
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Cushion Trax®
Recommended use	In manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual workstations. Also suitable for commercial environments including hotels, reception desks, shop counters, department stores, banks, restaurants, etc.
Series	Cushion Trax®
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Moselle, MS 39459, United States
Type	Dry Areas - Heavy Duty Industrial
Update trigger	20220209
Usage Intensity	Heavy duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	True
Recycled Material	60-70% recycled PVC top surface
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Warranty (years)	3

Tests

Abrasion Resistance 1000	0.41% weight loss
Abrasion Resistance 500	0.34% weight loss
Compression Deflection 1.4	0.43 cm
Compression Deflection 2.8	0.60 cm
Elongation	62,60%
Fire rating EU	EN 13501-1 Bfl-S1
Fire rating US	Pass
Foam Battery	40 lb/in ²
Hardness	85 Shore A
Slip Rating	R10
Coefficient Friction Dry	0,81
Surface Flammability	Pass
Tear Strength	34 lb

Technical Specifications

Application	Industrial Environments
Backing	Microcellular vinyl
Breaking Load	55 lb
Edges	Bevelled edges on all sides
Material	PVC
Material Group	PVC
Process	Lamination

B2 Athy Business Campus,
Athy,
Co. Kildare,
R14 PK74
01 5312777
sales@pittman.ie

pittman[®]

1310 Solihull Parkway,
Birmingham Business Park,
Birmingham,
B37 7YB
0121 630 3527
sales@pittman.uk