



Your guarantee of quality

OUTDOOR NOTICE BOARDS & POSTER DISPLAY CASES

"1000" 75 MM OUTDOOR NOTICE BOARDS

TECHNICAL SPECIFICATIONS

- HINGE FREE:** Wear resistant, warp proof integrated hinge.
- LOCKABLE:** Exclusive tamper-proof safety lock with hidden latch.
- FULL DISPLAY:** 100 % of the display surface visible (lock mounted in the frame not the glazing).
- STRENGTH:** Robust profile and available in 4mm anti-vandal Plexichoc™ or safety glass.
- PRACTICAL:** Doors easily replaceable in case of major vandalism.
- WATERPROOF:** Elastomer seal and anti-condensation vents.

NOTICE BOARD

- Format: single sided, raising or dual-door depending on dimensions.
- Display area: from 8 to 30 A4.
- Profile depth: 75 mm
- Glazing: vandal-resistant 4 mm Plexichoc® or 4 mm tempered safety glass.
- Opening method: side opening (door is reversible), dual-door or raising door.
- Raising doors: suspended on gas struts for easy opening and support.
- Locking: tamperproof safety lock with supplied 2 keys, two locks on H 1350 mm and raising door models.
- Waterproofing: elastomer seal.
- Back plate finish: galvanised steel back in a white lacquered finish for use with magnets. External back finished in RAL 7032 unless otherwise specified.
- Frame finish: silver anodised aluminium or painted in our Vitincom® colour offering.
- Installation: wall or post mounting (optional).
- Supplied with Procicity® magnets (1 per A4).

Optional post kits:

- Round ø 76 mm posts: 2 round ø 76 mm dove-tailed posts either silver anodised or painted with black lacquered steel top caps. Post kit contains 4 cast aluminium dove-tailed clamps for easy installation with no drilling required. Notice board adjustable in height.
- Installation: concrete directly in the ground
- Quatro post kit: 2 oblong 80 x 125 mm dove-tailed posts either silver anodised or painted with black lacquered steel top caps. Post kit contains 4 cast aluminium dove-tailed clamps for easy installation with no drilling required. Notice board adjustable in height.
- Installation: concrete directly in the ground or on base plates. *
- Quatro plus post: an oblong 80 x 125 mm dove-tailed posts either silver anodised or painted, delivered with contains 4 cast aluminium dove-tailed clamps.
- Installation: concrete directly in the ground or on base plates. *

*If the product is to be likely to be exposed to strong winds, we strongly recommend post kits to be concreted directly in the ground.

Optional header boards:

- Frame: 75mm aluminium profile, right angle corners matching the board.
- Signage surface: galvanised steel lacquered in white.
- Height: 220 mm.
- Installation: supplied with 2 cast aluminium dove-tailed

clamps for easy installation with no drilling required.

Other options:

LED kit (supplied for self-assembly) *

Additional magnets.

*LED ribbons and transformers are not factory fitted and require installation by a qualified electrician to comply with applicable safety regulations.

PAINT FINISH



RAL 5010



RAL 9005



RAL 3004



RAL 6005



RAL 8017



Anodised

