

345 Rubber Brush™

Rubber bristle entrance mat



Dust Control Matting - Loose Lay Scraper Mats 345 Rubber Brush™

Classic outdoor scraper mats stop dirt, grit and grime from entering the building. Made from a durable rubber compound, these mats withstand the heaviest of foot traffic, are easy to clean and practically weather proof.

- Bevelled edges improve safety and allow easy cart access
- Thousands of flexible fingers provide automatic shoe cleaning action when foot pressure is applied
- Moulded rubber backing has non-shifting suction cup design underneath

Recommended use

- Outdoor
- For placement inside entrances of hotels, shops, department stores, schools, universities, restaurants, supermarkets.
- Heavy traffic

Colors:

- Black

Sizes:

- 60cm x 80cm
- 80cm x 100cm
- 90cm x 150cm
- 90cm x 180cm

CRUSH RESISTANCE

RATING DUST CONTROL

B2 Athy Business Campus
Athy
Co. Kildare
R14 PK74
sales@pittman.ie
01 5312777

1310 Solihull Parkway
Birmingham Business Park
Birmingham
B37 7YB
sales@pittman.uk
0121 630 3527

Dust Control Matting - Loose Lay Scraper Mats Rubber Brush™

General

Brand	Notrax
Category	Loose Lay Scraper Mats
Product Number	345
Product Family	Industrial & Commercial Matting
Product Group	Dust Control Matting
Product Name	Rubber Brush™
Recommended use	For placement inside entrances of hotels, shops, department stores, schools, universities, restaurants, supermarkets.
Shipping Location	Barendrecht 2992SB, The Netherlands, Chicago, IL 60638, United States
Type	Indoor Absorbant - Loose Lay Carpet Mats
Update trigger	20210310-1301
Usage Intensity	Heavy traffic

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Reach US	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material, Contributes to a cleaner environment by reducing need of cleaning chemicals
Warranty	1

Tests

Fire rating US	Pass
Light Fastness	4.5
Sanitary Testing	Pass
Surface Flammability	Pass

Technical Specifications

Absorption Capacity	0.13 l/m ²
Accelerated Wear	4.5
Edges	Bevelled rubber borders on all four sides
Material	Natural rubber
Material Group	Natural rubber
Process	Compression Moulding